

FELT 2013年モデル規格表		0212年10月18日作成														
Fcarbon					F24		F95 Jr.		F75、F85、F95							
Size	48	51	54	56	40	44	48	51	54	56	58	48	51	54	56	58
HA	71	72.5	73	73.5	72	71.5	71	72.5	73	73.5	74	71	72.5	73	73.5	74
SA	74.5	74	73.5	73.5	73.5	75.5	74.5	74	73.5	73.5	73.5	74.5	74	73.5	73.5	73.5
TT Horiz	510	530	545	560	447	483	510	530	545	560	580	510	530	545	560	580
TT C-C	492	513	532	547	430	470	493	512	531	546	567	493	512	531	546	567
HT Length	100	110	120	140	120	130	100	120	130	150	170	100	120	130	150	170
Seat Tube C-T	440	480	520	540	345	400	440	470	520	540	570	440	470	520	540	570
Seat Tube C-C	392	432	472	492	290	365	391	422	472	492	522	391	422	472	492	522
BB Drop	72	70	70	70	30	49	72	70	70	70	70	72	70	70	70	70
BB Rise	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
OS	403	403	405	405	360	380	405	405	405	405	407	405	405	405	405	407
Front Center	577	578	580	588	493	551	577	579	580	588	604	577	579	580	588	604
Wheelbase	969	971	974	983	851	925	971	973	974	983	1000	971	973	974	983	1000
Standover	681	717	750	770	602	665	681	710	750	770	796	681	710	750	770	796
Fork Length	370	370	370	370	321	347	370	370	370	370	370	370	370	370	370	370
Rake	52	50	45	43	40	41	52	50	45	43	43	52	50	45	43	43
Lower HS Stack	1	1	1	1	12	1	1	1	1	1	1	1	1	1	1	1
Reach	370	381	389	397	314	358	370	379	386	395	409	370	379	386	395	409
Stack	500	514	526	548	448	489	500	523	536	557	578	500	523	536	557	578
Seat Post Dia.	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm
Seat Post Length	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm	300mm
	350mm (F1, F2)	350mm (F1, F2)	350mm (F1, F2)	350mm (F1, F2)												
Seat Post Clamp	27.3mm x 30.6mm double bolt	27.3mm x 30.6mm double bolt	27.3mm x 30.6mm double bolt	27.3mm x 30.6mm double bolt	31.8mm	30.6 (30.7 for painted frame)	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.	30.7mm for painted 30.6mm frame O.D.
Front Derailleur Clamp	Braze-on	Braze-on	Braze-on	Braze-on	31.8mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm	34.9mm
BB-Type (BB30, BSA,...)	BB30	BB30	BB30	BB30	English threaded	English threaded	BB30	BB30	BB30	BB30	BB30	BB30	BB30	BB30	BB30	BB30
	English threaded (F6)	English threaded (F6)	English threaded (F6)	English threaded (F6)			English threaded (F85,F95)	English threaded (F85,F95)	English threaded (F85,F95)	English threaded (F85,F95)	English threaded (F85,F95)	English threaded (F85,F95)	English threaded (F85,F95)			
BB-Shell Width	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm
O.L.D.	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm
RD-hanger Type	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable
Headset (Type)	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	Threadless 1.125"	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset.	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) x 1.5" (36° / 45°) For tapered 46mm/56mm OD				
	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F6)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F6)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F6)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F6)			FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headset. (F95)			
Stem Length	80mm	90mm	100mm	100mm	80mm	80mm	80mm	90mm	100mm	100mm	110mm	80mm	90mm	100mm	100mm	110mm
Handlebar Width C-C	380mm	400mm	420mm	420mm	370mm	360mm	380mm	400mm	420mm	420mm	440mm	380mm	400mm	420mm	420mm	440mm
Crank Length	165mm	170mm	172.5mm	172.5mm	155mm	160mm	165mm	170mm	172.5mm	172.5mm	175mm	165mm	170mm	172.5mm	172.5mm	175mm

FELT 2013年モデル規格表	0212年10月18日作成											
Z1, Z2, Z3, Z4, Z5, Z6,					Z75, Z85, ZA				Z95, Z100 700c			
Size	51	54	56	58	51	54	56	58	51	54	56	58
HA	72	72.5	72.5	72.5	72	72.5	72.5	72.5	72	72.5	72.5	72.5
SA	74.5	74	73.5	73	74.5	74	73.5	73	74.5	74	73.5	73
TT Horiz	525	545	560	575	525	545	560	575	525	545	560	575
TT C-C	507	524	538	551	507	526	540	553	507	526	540	553
HT Length	140	160	180	200	140	160	180	200	140	160	180	200
Seat Tube C-T	470	500	520	540	470	500	520	540	470	500	520	540
Seat Tube C-C	415	425	445	465	425	445	465	485	425	445	465	485
BB Drop	70	70	70	70	70	70	70	70	70	70	70	70
BB Rise	-	-	-	-	-	-	-	-	-	-	-	-
CS	417	417	417	417	417	417	417	417	417	417	417	417
Front Center	583	595	605	615	584	595	605	615	584	595	605	615
Wheelbase	990	1002	1012	122	990	1002	1012	1022	990	1002	1012	1022
Standover	698	727	747	767	713	726	746	765	713	726	746	765
Fork Length	370	370	370	370	370	370	370	370	370	370	370	370
Rake	50	50	50	50	50	50	50	50	50	50	50	50
Lower HS Stack	1	1	1	1	1	1	1	1	1	1	1	1
Reach	373	384	388	392	374	384	388	392	374	384	388	392
Stack	541	561	580	600	541	561	580	600	541	561	580	600
Seat Post Dia.	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm
Seat Post Length	330mm	330mm	330mm	330mm	330mm	330mm	330mm	330mm	330mm	330mm	330mm	330mm
	350mm (Z1,Z2)	350mm (Z1,Z2)	350mm (Z1,Z2)	350mm (Z1,Z2)								
Seat Post Clamp	30.6mm	30.6mm	30.6mm	30.6mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm
Front Derailleur Clamp	Braze-on	Braze-on	Braze-on	Braze-on	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm	31.8mm
BB-Type (BB30, BSA,...)	BB02 (Z1)	BB02 (Z1)	BB02 (Z1)	BB02 (Z1)	BB30 (Z75)	BB30 (Z75)	BB30 (Z75)	BB30 (Z75)				
	English threaded (Z6)	English threaded (Z6)	English threaded (Z6)	English threaded (Z6)	English threaded	English threaded	English threaded	English threaded	English threaded	English threaded	English threaded	English threaded
	BB30	BB30	BB30	BB30								
BB-Shell Width	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm
O.L.D.	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm
RD-hanger Type	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable
Headset (Type)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°)	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°)
	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	For tapered 46mm/56mm OD	42mm OD headtube.	42mm OD headtube.	42mm OD headtube.	42mm OD headtube.
Stem Length	80mm	90mm	100mm	110mm	80mm	90mm	100mm	110mm	80mm	90mm	100mm	110mm
Handlebar Width C-C	400mm	420mm	420mm	440mm	400mm	420mm	420mm	440mm	400mm	420mm	420mm	440mm
Crank Length	170mm	172.5mm	172.5mm	175mm	170mm	172.5mm	172.5mm	175mm	170mm	172.5mm	172.5mm	175mm

FELT 2013年モデル規格表		0212年10月18日作成					
ZW2, ZW3, ZW4, ZW5				ZW75, ZW85, ZW95			
Size	Petite	Small	Medium	43	45	47	50
HA	70.25	71.25	72	70.25	71.5	72	72.5
SA	75.25	74.5	74.5	75.25	74.5	74.5	74
TT Horiz	495	512	525	495	514	525	545
TT C-C	479	494	507	479	496	507	526
HT Length	120	130	140	110	125	140	160
Seat Tube C-T	430	450	470	430	450	470	500
Seat Tube C-C	375	395	415	385	405	425	445
BB Drop	72	72	70	72	72	70	70
BB Rise	-	-	-	-	-	-	-
CS	410	410	417	410	410	417	417
Front Center	576	578	583	575	578	584	595
Wheelbase	974	977	990	974	977	990	1002
Standover	-	-	-	675	694	713	726
Fork Length	370	370	370	370	370	370	370
Rake	52	52	50	52	52	50	50
Lower HS Stack	1	1	1	1	1	1	1
Reach	357	363	373	359	367	374	384
Stack	517	530	541	507	526	541	561
Seat Post Dia.	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm
Seat Post Length	300mm	300mm	300mm	300mm	300mm	300mm	300mm
Seat Post Clamp	30.6	30.6	30.6	31.8mm	31.8mm	31.8mm	31.8mm
Front Derailleur Clamp	Braze-on	Braze-on	Braze-on	31.8mm	31.8mm	31.8mm	31.8mm
BB-Type (BB30, BSA,...)	BB30	BB30	BB30	BB30	BB30	BB30	BB30
	English threaded (ZW5)	English threaded (ZW5)	English threaded (ZW5)	BB30	BB30	BB30	BB30
BB-Shell Width	68mm	68mm	68mm	68mm	68mm	68mm	68mm
O.L.D.	130mm	130mm	130mm	130mm	130mm	130mm	130mm
RD-hanger Type	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable
Headset (Type)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.
Stem Length	60mm	70mm	80mm	60mm	70mm	80mm	90mm
Handlebar Width C-C	380mm	380mm	380mm	380mm	380mm	380mm	400mm
Crank Length	165mm	165mm	170mm	165mm (ZW75)	170mm (ZW75)	170mm (ZW75)	172.5mm (ZW75)
				165mm	165mm	170mm	172.5mm

AR1, AR2, AR3, AR4, AR5

Size	51	54	56	58
HA	72.5	73	73.5	73.5
SA	74.5	73.5	73.125	73
TT Horiz	530	545	560	575
TT C-C	521	542	555	570
HT Length	120	140	160	180
Seat Tube C-T	510	540	560	580
Seat Tube C-C	470	498	518	538
BB Drop	70	70	70	70
BB Rise	-	-	-	-
CS	412	412	415	415
Front Center	578	581	584	598
Wheelbase	980	983	989	1002
Standover	749	774	794	798
Fork Length	365	365	365	365
Rake	45	45	43	43
Lower HS Stack	1	1	1	1
Reach	385	386	389	398
Stack	520	541	562	581
Seat Post Dia.	Aero	Aero	Aero	Aero
Seat Post Length	300mm	300mm	300mm	300mm
Seat Post Clamp	Felt aero clamp	Felt aero clamp	Felt aero clamp	Felt aero clamp
Front Derailleur Clamp	Braze-on	Braze-on	Braze-on	Braze-on
BB-Type (BB30, BSA,...)	English threaded	English threaded	English threaded	English threaded
BB-Shell Width	68mm	68mm	68mm	68mm
O.L.D.	130mm	130mm	130mm	130mm
RD-hanger Type	Replaceable	Replaceable	Replaceable	Replaceable
Headset (Type)	FSA Orbit IS-2 Integrated 1-1/8" (36° /45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° /45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° /45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° /45°) 42mm OD headtube.
Stem Length	90mm	100mm	100mm	110mm
Handlebar Width C-C	400mm	420mm	420mm	440mm
Crank Length	170mm	172.5mm	172.5mm	175mm

FELT 2013年モデル規格表												
0212年10月18日作成												
	650c: B2, B12, B14, B16, B16W	700c: B2, B12, B14, B16, B16W			650c: S32	700c: S32			DA			
Size	47	51	54	56	47	51	54	56	47	51	54	56
HA	71	72.5	73	73	71	72	72.5	72.5	71	72.5	73	73
SA	76.5	76	76	76	78.8	78	78	78	76.5-78.8	76-78.1	76-78	76-78
TT Horiz	490	518	539	614	466	496	518	538	471-490	500-520	521-540	541-560
TT C-O	-	515	540	580	-	-	-	-	490	520	540	560
HT Length	115	115	127	147	120	120	130	150	78	80	88	108
Seat Tube C-T	470	510	540	560	470	510	540	560	470	510	540	560
Seat Tube C-O	-	-	-	-	410	450	480	500	455	495	525	545
BB Drop	45	70	71	72	45	70	70	70	45	70	70	70
BB Rise	-	-	-	-	-	-	-	-	-	-	-	-
CS	375	395	395	395	375	395	395	395	375	395	395	395
Front Center	565	577	593	614	565	582	599	621	565	577	593	614
Wheelbase	935	961	978	999	935	967	984	1006	935	962	978	999
Standover	-	-	-	-	-	-	-	-	724	770	794	813
Fork Length	345	370	370	370	345	370	370	370	345	370	370	370
Rake	40	40	40	40	41	43	43	43	40	40	40	40
Lower HS Stack	1	1	1	1	1	1	1	1	1	1	1	1
Reach	375	388	405	420	373	385	403	419	387	399	416	432
Stack	468	521	536	556	472	524	535	554	433	488	497	516
Seat Post Dia.	Felt Aero	Felt Aero	Felt Aero	Felt Aero	27.2mm	27.2mm	27.2mm	27.2mm	Felt Aero	Felt Aero	Felt Aero	Felt Aero
Seat Post Length	350mm	350mm	350mm	350mm	300mm	300mm	300mm	300mm	350mm	350mm	350mm	350mm
	300mm (B16)	300mm (B16, B16W)	300mm (B16, B16W)	300mm (B16, B16W)								
Seat Post Clamp	Felt aero clamp	Felt aero clamp	Felt aero clamp	Felt aero clamp	30.6 (30.7 for painted frame)	30.6 (30.7 for painted frame)	30.6 (30.7 for painted frame)	30.6 (30.7 for painted frame)	Felt integrated aero clamp	Felt integrated aero clamp	Felt integrated aero clamp	Felt integrated aero clamp
Front Derailleur Clamp	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on	Braze-on
BB-Type (BB30, BSA,...)	BB30	BB30	BB30	BB30	English threaded	English threaded	English threaded	English threaded	BB30	BB30	BB30	BB30
	English threaded (B16)	English threaded (B16, B16W)	English threaded (B16, B16W)	English threaded (B16, B16W)								
BB-Shell Width	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm	68mm
O.L.D.	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm	130mm
RD-hanger Type	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Headset (Type)	IS-2	IS-2	IS-2	IS-2	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	FSA Orbit IS-2 Integrated 1-1/8" (36° / 45°) 42mm OD headtube.	19mm OD, integrated Bayonet type	19mm OD, integrated Bayonet type	19mm OD, integrated Bayonet type	19mm OD, integrated Bayonet type
Stem Length	60mm	80mm	90mm	90mm	60mm	80mm	90mm	90mm	Rise: 30mm x Ext: 70mm	Rise: 30mm x Ext: 70mm	Rise: 30mm x Ext: 70mm	Rise: 60mm x Ext: 100mm
Handlebar Width C-O	390mm	60mm (B16W)	80mm (B16W)	90mm								
		390mm	390mm	420mm	390mm	390mm	390mm	420mm	390mm	390mm	390mm	420mm
Crunk Length	165mm	170mm	172.5mm	175mm	165mm	170mm	172.5mm	175mm	165mm	170mm	172.5mm	175mm

FELT 2013年モデル規格書	0212年10月18日作成				
	F1X, F2X, F3X, F4X, F5X, F6X, F75X				
Size	47	50	53	55	57
HA	71	71.5	72	72	72
SA	75	74.5	73.5	73.8	73
TT Horiz	510	525	540	560	580
TT C-C	495	510	525	543	583
HT Length	110	120	130	150	170
Seat Tube C-T	470	500	530	550	570
Seat Tube C-C	410	440	470	490	510
BB Drop	65	65	65	65	65
BB Rise	-	-	-	-	-
DS	430	430	430	430	430
Front Center	583	584	585	605	620
Wheelbase	1005	1005	1007	1027	1042
Standover	726	751	779	796	814
Fork Length	393	393	393	393	393
Rake	50	45	45	45	45
Lower HS Stack	1	1	1	1	1
Reach	368	375	377	391	400
Stack	525	538	549	568	587
Seat Post Dia.	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm
Seat Post Length	300mm (FIX 350mm)	300mm (FIX 350mm)	300mm (FIX 350mm)	300mm (FIX 350mm)	300mm (FIX 350mm)
Seat Post Clamp	31.8mm carbon frame/20.6 alloy frame	31.8mm carbon frame/20.6 alloy frame	31.8mm carbon frame/20.6 alloy frame	31.8mm carbon frame/20.6 alloy frame	31.8mm carbon frame/20.6 alloy frame
Front Derailleur Clamp	31.8mm carbon frame/24.8mm alloy frame	31.8mm carbon frame/24.8mm alloy frame	31.8mm carbon frame/24.8mm alloy frame	31.8mm carbon frame/24.8mm alloy frame	31.8mm carbon frame/24.8mm alloy frame
BB-Type (BB30, BSA...)	BB30	BB30	BB30	BB30	BB30
BB-Shell Width	68mm	68mm	68mm	68mm	68mm
O.L.D.	135mm	135mm	135mm	135mm	135mm
RD-hanger Type	Replaceable	Replaceable	Replaceable	Replaceable	Replaceable
Headset (Type)	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD	FSA NO.42 Integrated 1-1/8" (45° / 45°) × 1.5" (36° / 45°) For tapered 46mm/56mm OD
Stem Length	70mm (F1X) 80mm	80mm (F1X) 90mm	90mm (F1X) 100mm	100mm (F1X) 100mm	110mm (F1X) 110mm
Handlebar Width C-C	450mm (F1X) 380mm	450mm (F1X) 400mm	470mm (F1X) 420mm	470mm (F1X) 440mm	470mm (F1X) 440mm
Crank Length	165mm	170mm	172.5mm	175mm	175mm

FELT 2013年モデル規格表	0212年10月18日作成									
QX SUSPENSION					QX Rigid					
Size	44	44L	48	52	55	44	48	52	55	
HA	70	70.5	70.5	71	71.5	70	70.5	71	71.5	
SA	74.5	72.5	73	72.75	72.5	74.5	73	72.75	72.5	
TT Horiz	541	558	568	578	589	541	568	578	589	
TT C-C	523	569	545	553	563	525	545	556	567	
HT Length	110	140	130	130	150	150	160	170	190	
Seat Tube C-T	440	440	480	520	550	440	480	520	550	
Seat Tube C-C	375	240	415	455	485	375	415	455	485	
BB Drop	55	55	55	55	55	55	55	55	55	
BB Rise	-	-	-	-	-	-	-	-	-	
CS	445	445	445	445	445	445	445	445	445	
Front Center	616	606	621	623	626	612	619	622	625	
Wheelbase	1055	1045	1060	1062	1065	1052	1058	1061	1064	
Standover	730	619	767	801	828	720	754	788	842	
Fork Length	476	476	476	476	476	393	393	393	393	
Rake	38	38	38	38	38	38	38	38	38	
Lower HS Stack	1	1	1	1	1	1	1	1	1	
Reach	377	362	380	387	389	388	396	400	401	
Stack	594	624	614	617	638	553	565	576	597	
Seat Post Dia.	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	27.2mm	
Seat Post Length	27.2 mm x 300 mm					27.2 mm x 300 mm				
Seat Post Clamp	34.9 mm x 11 mm					34.9 mm x 11 mm				
Front Derailleur Clamp	34.9 mm x 63-66 degree					34.9 mm x 63-66 degree				
BB-Type (BB30, BSA,...)	BSA					BSA				
BB-Shell Width	73 mm					73 mm				
O.L.D.	135 mm					135 mm				
RD-hanger Type	QX SPECIFIC					QX SPECIFIC				
Headset (Type)	No.10 Zero Stack 1-1/8" 50mm OD/44mm ID					No.10 Zero Stack 1-1/8" 50mm OD/44mm ID				
Stem Length	70 mm	70 mm	70/ 80* mm	90 mm	105 mm	70 mm	70/ 80* mm	90 mm	105 mm	
Handlebar Width C-C	620 mm	620 mm	620 mm	640 mm	640 mm	600 mm				
Crank Length	170 mm	170 mm	170 mm	170 mm	175 mm	170 mm	170 mm	170 mm	175 mm	
	* stem length QX80/90/100					* stem length QX85/95				